

Bopp Matte Film (Low Fish-Eye Grade)

- **Application:** BOPP matt film apply to printing&lamination.
- **Characters:**Excellent matt effect Very less crystal spots Comfortable hands feeling
High haze and low gloss Perfect ink adhesion and lamination strength
- **Surface treatment:**One side or both sides
- **Standard thickness:** 12/15μm

PROPERTIES		TEST METHOD	UNIT	TYPICAL DATA
MECHANICAL PROPERTIES				
Tensile strength	MD	ASTM D882	N/mm ²	≥120
	TD			≥140
Elongation at break	MD	ASTM D882	%	≤200
	TD			≤75
PHYSICAL PROPERTIES				
Coefficient of friction		ASTM D1894	/	≤0.7
Density		ASTM D792	g/cm ³	0.84
Gloss	Matte side	ASTM D2457	%	≤15
Haze		ASTM D1003	%	≥70
THERMAL PROPERTIES				
Heat shrinkage	MD	ASTM D1204 120°C/2min	%	≤3.5
	TD			≤2.0
OTHER PROPERTIES				
Surface tension	Corona side	ASTM D2578	Dyne	≥38

All details of product sold represent the best condition available to us, and we believe them to be reliable, which can not be guaranteed. We suggest that the suitability is determined by the really requirements of buyers.