

Bopp Transparent Film

- **Application:** BOPP plain film apply to food and commodity package.Especially for rotogravure printing.
- **Characters:**Good performance in rotogravure printing Good transparency Excellent ink adhesion
Excellent oil resistance High tensile strength
- **Surface treatment:** One side
- **Standard thickness:** 18/20/25/28/38/40μm

PROPERTIES		TEST METHOD	UNIT	TYPICAL DATA
MECHANICAL PROPERTIES				
Tensile strength	MD	ASTM D882	N/mm ²	≥140
	TD			≥260
Elongation at break	MD	ASTM D882	%	≤180
	TD			≤65
PHYSICAL PROPERTIES				
Coefficient of friction		ASTM D1894	/	≤0.6
Density		ASTM D792	g/cm ³	0.91
Gloss		ASTM D2457	%	≥90
Haze		ASTM D1003	%	≤2.0
THERMAL PROPERTIES				
Heat shrinkage	MD	ASTM D1204 120°C/2min	%	≤3.5
	TD			≤2.0
OTHER PROPERTIES				
Surface tension	Corona side	ASTM D2578	Dyne	≥38

All details of product sold represent the best condition available to us, and we believe them to be reliable, which can not be guaranteed. We suggest that the suitability is determined by the really requirements of buyers.